

megamount 851-2

LKW-Montiermaschine

Heavy duty tyre changer



Heavy duty tyre changer with a 90 degree angle between chuck and tool. For trucks, agricultural and earthmoving vehicles.



This is self-evident for us:

- Movable control
- 2 speed rotation chucking table and tools holder
- Adjustable working pressure
- Clamping range 14" –56"
- Tyre width maximal 1.500 mm (57")
- Tyre diameter maximal 2500 mm (96")

For all problems the right solution :

- | | |
|-----------------------------|--|
| • INTEGRAL MOVEMENT | Chuck holder and tool holder always work on the same plane, for a perfect angle of the operating tool against tyre bead. |
| • CONTROL UNIT | The movable control unit allows the operation out of any position |
| • WORKING SPEED | Two speeds ensure a quick operation without damaging tyre and rim |
| • CLAMPING HEAD | The hydraulic pressure of the rim clamping can be adjusted. So any damage of the rim is avoided. |
| • FULLY AUTOMATIC FUNCTIONS | All movements of the machine are fully automatic. This ensures the most easy, and also the most safe handling of all functions |

This comes with the machine



Technical Data	
Clamping Range	14"-56"
Max. wheel weight	2000 kg
Max. wheel diameter	2500 mm (96")
Max. wheel width	1500 mm (57")
Hydraulic pump motor	3 kW 400 V-3PH
Gearbox motor	1,5 – 2,3 kW 400 v-3PH
Operating pressure	0 - 160 bar
Bead breaker force inside-outside	3.364 kg
Noise level in working condition	< 70 db
Net weight	1.300 kg
Dimensions	W. 3.150 x D. 2.600 x H. 1.970 mm

Abmessungen:

